

## FA3820 CO ALARM WITH 10 YEAR BATTERY


<b>Sensor type</b>	ADVANCED ELECTROCHEMICAL
<b>Battery type</b>	SEALED FOR LIFE LITHIUM BATTERY




- 10 year life featuring a 10 year sealed for life lithium battery
- Advanced electrochemical sensor calibrated and tested in CO gas
- Ventilate 'Pre alarm' warning: Low level monitoring function
- Quiet test function supports discreet testing at a lower volume when compared to standard CO alarms
- Intelligent algorithm heightens the sensitivity when detection of low level CO occurs - providing a rapid alert to dangerous CO levels
- Memory function – indication of previous alarm activation
- Advanced diagnostics support via cable
- Prominent visual alarm notification

Please note markings may vary depending on Country

## Technical Specification



<b>Dimensions</b>	125mm (width) x 67mm (height) x 33mm (depth)	
<b>Supply voltage</b>	3V DC	
<b>Battery</b>	10 year sealed for life lithium battery	
<b>Sensor Technology</b>	Advanced Electrochemical	
<b>Alarm sound level</b>	85dB(A) at 3m (minimum)	
<b>Installation positions</b>	Wall / Free-standing ( <i>Portable - suitable for home and/or travel use</i> )	
<b>For use in</b>	Domestic premises including static and mobile homes, caravans, motor caravans and boats.*	
<b>Operating temperature</b>	-10 °C to +40 °C	
<b>Operating humidity</b>	30 - 90% RH	
<b>Storage temperature</b>	-20 °C to +50 °C	
<b>Storage humidity</b>	30-90% RH (non condensing)	
<b>Plastic material</b>	Fire Retardant ABS	
<b>Warranty</b>	5 years	
<b>Certified to</b>	BS EN 50291-1:2018, BS EN 50291-2:2019	
<b>Independently tested by</b>	BSI (certificate number KM 551504)	
<b>Weight</b>	95g	

